

SUBRA2 Patch & Splice 2U Shelf



FOCUS-SUBRA2-xxR2 is a pivoting 2U shelf suitable to splice and patch fibre optic cables using the most common connector types (SC, LC, etc.). It can easily integrate splitters, WDMs and any other passive devices.

The shelf is made of a fixed unit (19" or ETSI standard) to be mounted in the rack and of a pivoting tray where splice trays and connectors are pre-installed. Removable front cover and pivoting tray allow easy patchcord installation and re-accessibility.

Angled patch panel reduce the risk of eye damage.

Minimum bending radius 30 mm is guaranteed.

Cable entrance is on the left side of the shelf and patchcords exit is on the right front side.

The shelf can be provided with pigtailed and adaptors pre-installed according to the need.

KEY FEATURES AND BENEFITS

Accommodate up to 96 patching SC-style in only 2HU shelf

Pivoting shelf for easy installation and maintenance

Full bend radius control, very easy installation

Pre-loaded pigtailed on request

APPLICATIONS

High density splices and multi-cables interconnections

Inside and Outside plants installations

Future proof for high density demanding applications



DIMENSIONS AND CAPACITIES

PARAMETERS		UNIT	19"	ETSI METRIC
			Height	87.5 (2HU 3.5 inches)
Dimensions (without flanges)	Width	mm	445	491
	Depth		280	
Material	Mild steel			
Weight		kg	5	6.3
Colour	Powder coated 7035			

CAPACITIES		19"	ETSI METRIC
Connectors (SC type)		96	96
Splicing – Single Circuit Management	2 f.o.	24	48
Splicing – Single Element Management	12 f.o.	96	144